

EC CERTIFICATE OF CONFORMITY

0432 – CPD – 0141

In compliance with *Council Directive 89/106/EEC of 21 December 1988 on the approximation of laws, regulations and administrative provisions of the Member States relating to construction products* (the Construction Products Directive or CPD), as later amended, it has been stated that the construction product

Door Closer DORMA TS Profil

controlled door closing devices as detailed on appendix 1,

placed on the market

**DORMA GmbH & Co. KG
DORMA Platz 1
D-58256 Ennepetal**

and produced in the factory

manufacturing plant DO 2.20

is submitted by the manufacturer to a factory production control *and to the further testing of samples taken at the factory in accordance with a prescribed test plan* and that the notified body No. < 0432n > - < MPA NRW > - has performed the initial type-testing for the relevant characteristics of the product, the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control.

This certificate attests that all provisions concerning the attestation of conformity and the performances described in Annex ZA of the standard

**DIN EN 1154: 2003-04
(EN 1154:1996 + A1:2002 D)**

were applied and that the product fulfils all the prescribed requirements.

This certificate was first issued on 04.14. 2010 and remains valid as long as the conditions laid down in the harmonised technical specification in reference or the manufacturing conditions in the factory or the FPC itself are not modified significantly.

Dortmund, 04.14. 2010



Dipl.-Ing. H. Jansen
deputy head of certification body

THIS CERTIFICATE COMPRISES ONE (1) PAGE AND ONE (1) APPENDIX

Marsbruchstraße 186 • 44287 Dortmund-Aplerbeck • Telefon (0231) 4502-480 • Telefax (0231) 4502 586 • Internet www.mpanrw.de

This document was originally written in German. In case of doubt the German version shall prevail.

List of products

Type :	DORMA TS Profil EN2/3/4 BCA
Description :	Rack and pinion door closer, adjustable backcheck, closing speed adjustable via two independent valves (180°-15°, 15°-0°), selectable closing force
Arm :	Projecting arm
Installation :	Door-leaf fixing pull side (standard installation),
Door closer power size :	EN 2/3/4
Classification :	4 8 2/3/4 1 1 3
Remarks :	For use on fire / smoke the door closer power size shall be adjusted on site to size 3 or more.
Type :	DORMA TS Profil EN2/3/4 BCA
Description :	Rack and pinion door closer, adjustable backcheck, closing speed adjustable via two independent valves (180°-15°, 15°-0°), selectable closing force
Arm :	Projecting arm
Installation :	Frame fixing push side
Door closer power size :	EN 2/3/4
Classification :	3 8 2/3/4 1 1 3
Remarks :	For use on fire / smoke the door closer power size shall be adjusted on site to size 3 or more.